

Black Label Collection
[Chased Effect | Solid | 3/4"]

#760 CE-S, #761 CE-S, #762 CE-S, #764 CE-S, #765 CE-S,
#770 CE-S, #771 CE-S, #772 CE-S, #773 CE-S, #780 SM-S
#790 SM-S

SERIES INFORMATION:

Colors:	Species/Janka	Thickness	Width	Length	Wear Layer	SF/BOX	BX/PLT	SF/PLT	BX/WGT	SF/WGT	Waste %
#760 CE-S-#765 CE-S	Red Oak (1280)	3/4"	3 1/4"	1'-7'	1/4"	20.00	52	1040	58	2.9 lbs	6-8%
#770 CE-S-#773 CE-S	Silver Maple (960)	3/4"	3 1/4"	1'-7'	1/4"	20.00	52	1040	53	2.65 lbs	6-8%
#780 SM-S	Hard Maple (1400)	3/4"	3 1/4"	1'-7'	1/4"	20.00	52	1040	60	3 lbs	4-6%
#790 SM-S	Red Oak (1280)	3/4"	3 1/4"	1'-7'	1/4"	20.00	52	1040	58	2.9 lbs	4-6%

INSTALLATION

- ☒ Nail
- ☒ Nail/Glue Assist (Preferred)
- ☒ Glue Only (with limitations)
- ☒ Float
- ☒ Below Grade
- ☒ Click
- ☒ Radiant Heat

ADDITIONAL INFORMATION:


Core Construction	Solid Wood
Joint System	Tongue and Groove
Texture	Chased Effect
Edge Profile	Micro Bevel
Finish Type	Model Plus polyurethane infused with alluminum oxide
Gloss Levels	4%-5%
Maintenance	Bona Hardwood Formula
Repair Finish	Can be screened and recoated with Bona HD Traffic (or similar)
Expansion Requirements	Requires 1/2" expansion gap
Fastener Requirements	15-16 gauge L/T cleats or 7/16" to 1/2" crown staples (minumum 1 3/4" Length). Fastener spacing 1 1/2" from the board ends and every 6" - 8" along the tongue
Uses	Residential Light Duty Commercial

COMPLIANCE:

This series has been tested and contains the following certifications:



877.238.3225 | www.my-nfp.com



LIMITED WARRANTY

Finish: 25 year
Structural: Lifetime

COMMON QUESTIONS:

SUBSTRATE REQUIREMENTS

Structurally sound, well bounded, flat to within 3/16" in 10' radius, or 1/8" in 6' radius. Vertical deflection cannot exceed 1/4" in 10' radius, or more than 1/16" between the floor joist.

APPROVED SUBSTRATES

Underlayment APA grade CDX plywood/OSB. See NWFA guidelines for 3000 PSI concrete or 2500 PSI gypcrete.

WOOD SUBFLOOR (EMC) MOISTURE CONTENT REQUIREMENTS

Solid wood MC (moisture content) must test within 2% of the wood subfloor. Neither can exceed 12%.

CONCRETE AND GYPCRETE MOISTURE EMISSIONS, RH, AND PH REQUIREMENTS

Random width and/or narrower than 4 1/4" ONLY. Check with NWFA for an approved adhesive and/or moisture mitigation system for concrete/gypcrete, RH, pH, and installation requirements. (Bond and moisture mitigation warranties comes solely from glue and/or vapor barrier manufacturer.)

JOBSITE CONDITION RANGES

Prior, during, and after installation, the jobsite RH must be maintained between 35-55%, and the room temperature between 60-80°F.

ACCLIMATION TIME FRAME

Minimum 72 hours to reach room temperature between 60-80 °F. The subfloor and the wood flooring MC (moisture content) must test within 2% of each other and does exceed 12%. If the MC falls outside this range, a longer acclimation period is required to reach equilibrium.

CAN WE INSTALL A CUSHION UNDERNEATH THE FLOOR?

Cushion is not compatible.

RUG COMPATIBILITY

Must be breathable, non abrasive, natural fiber rugs. Please see RugPadUSA.com. For example; Eco Plush 3/8", Contour Lock, RugPro, or Superior Lock 1/4".



Note: For accuracy, we used actual material to create these product images. Please be aware that colors on printed media or displayed on a screen may vary from the actual product.



Chased Effect

Black Label Collection
[Chased Effect | Solid | 3/4"]



CHASED EFFECT



Color # 770 CE-S Silver Maple



Color # 760 CE-S Red Oak



Color # 771 CE-S Silver Maple



Color # 761 CE-S Red Oak



Color # 772 CE-S Silver Maple



Color # 762 CE-S Red Oak



Color # 773 CE-S Silver Maple



Color # 764 CE-S Red Oak



Color # 780 SM-S Hard Maple



Color # 765 CE-S Red Oak



Color # 790 SM-S Red Oak