

## EX EXPEDITION COLLECTION

Expedition Collection  
 [Wood Grain | SPC | 6MM]

#1400 WG-RIG, #1401 WG-RIG, #1402 WG-RIG, #1403 WG-RIG  
 #1404 WG-RIG, #1405 WG-RIG, #1406 WG-RIG, #1407 WG-RIG  
 #1408 WG-RIG, #1409 WG-RIG, #1410 WG-RIG

### SERIES INFORMATION:

Colors:	Thickness	Width	Length	Wear Layer	SF/BOX	BX/PLT	SF/PLT	BX/WGT	SF/WGT	Waste %
#1400 WG-RIG-#1410 WG-RIG	6MM	7 1/4"	60"	20MIL	24.02	60	1441	45	1.87 lbs	4-6%

### INSTALLATION

- ☒ Nail
- ☒ Float
- ☒ Radiant Heat
- ☒ Nail/Glue Assist
- ☒ Click
- ☒ Glue Only
- ☒ Below Grade

### ADDITIONAL INFORMATION:


Core Construction	Tuffcore SPC (Polyvinyl Chloride)
Core Type	SPC (Virgin) 2000+ PSI
Joint System	I4F Triple Lock
Texture	Wood grain
Edge Profile	Painted Bevel 1.2mm
Finish Type	2 Coats of UV cured urethane infused with ceramic.
Gloss Levels	5 - 7%
Maintenance	ZEP Neutral Floor Cleaner
Repair Finish	Dr. Schutz Scratch Fix - Vinyl Design Floor Repair
Expansion Requirements	1/4" expansion gap for the first 20 Lineal feet (length or width). Add additional 1/16" for every 5' of install (length or width) upto 1/2". T-molds are required for rooms exceeding 60 lineal feet in length and width and 50 lineal feet for installations over in floor radiant heat.
Uses	Residential - Commercial

### COMPLIANCE:

This series has been tested and contains the following certifications:



877.238.3225 | www.my-nfp.com



### LIMITED WARRANTY

Finish: Limited Lifetime  
 Structural: 10 year Commercial

### COMMON QUESTIONS:

#### SUBSTRATE REQUIREMENTS

Structurally sound, well bounded, flat to within 3/16" in 10' radius or 1/8" in 6' radius, vertical deflection cannot exceed 1/4" in 10' Radius, or more than 1/16" between the floor joist.

#### APPROVED SUBSTRATES

Underlayment APA grade CDX plywood/OSB, 3000 PSI concrete or 2500 PSI gypcrete. Underlayment grade MDF. See installation guide for additional approved substrates.

#### WOOD SUBFLOOR (EMC) MOISTURE CONTENT REQUIREMENTS

Should not exceed 12% MC (moisture content).

#### CONCRETE AND GYPCRETE MOISTURE EMISSIONS, RH, AND PH REQUIREMENTS

Properly install a minimum of 6mil plastic over the entire substrate. Overlap all seams 12" and tape all seams with moisture proof tape.

#### JOBSITE CONDITION RANGES

RH between 30-60% and room temperature between 60 to 80°F. Post installation temperature range must be within 10 to 142°F.

#### ACCLIMATION TIMEFRAME

No acclimation is required if the product was stored and/or transported in 60 to 80°F for at least 24 hours prior to installation. Otherwise, it must acclimate for a minimum of 24 hours. Please see installation guide for radiant heat application.

#### CAN WE INSTALL A CUSHION UNDERNEATH THE FLOOR?

This product has an attached 1.5mm thick high density EVA cushion. An additional cushion is not compatible.

#### RUG COMPATIBILITY

Must be breathable, non abrasive, natural fiber rugs. Please see RugPadUSA.com. For example; Anchor Grip, Nature's Grip, RugPro, or Super Lock Natural.



## EX EXPEDITION COLLECTION

Expedition Collection  
[Wood Grain | SPC | 6MM]



WOOD GRAIN

